Section 5 Town 8	Range 4-	- August 4	1830 =					4		
100	I comm	nenced a Survey of Section 546, T. 8	8.4.	CORNER ESTABLISHED.		WITNESS POINTS OR BEARING TREES.	Mark or Dia. in Inches.	COURSE.	Links Distant.	REMARKS.
	Mar Welly 12 32/3 Chain Park H Lo Trues	la William J pan Crocky Jawan	209 109, 109, 109, 109, 109, 109, 109, 10	A 13 ch from SE ONE  It E from Center  It S of above stone  It W of SE  I Chapter of Center  I Stone Set  I Chapter of Section  I Stone Set  I Chapter Set  I Chapter Sect  I Chapter	Sandstone 5x5x14" X Center 5x5x14" X Center 5x14 X Center 6x14x14 X Center 6x14x14 X Center 6x14x14" X Center 6x14x14" X Ceter	Sycamore 1948  Ash  Sycamore  Elmi  Elmi  Cherry  White Oak  Quant  Maple  Elmi  Maple  Cottonwood	16"	N 2° E N 86° E S 32° 15' E N 84° 30' E N 50° 40' E N 50° 40' E N 60° E N 60° E N 60° E S 45° W S 45° W S 45° W	241.75 241.75 7.4 Pt 32.6 Pt 106.4 Pt 38.5 Pt 28.6 Pt 44.6 Pt 14.5 Pt 14.5 Pt 15.2 Pt	
Var.  SENTINE FOR THE PROPERTY OF THE PROPERTY		Best Crane Surveyor	Logarty Sulo V Freede County. 60 17	13 Ch, From Center on North Sid went Creeke Curty Line + 8,00 South	and +	Maple		8 80° 45' E N 89° 50' W N 81° E S 89° 35' W	88.5 # 61,2 # 71.4 # 15.8 #	
SECURE 32.13  E Center Sect 209 ft  S From Stoneset 209 ft  W II II 16,84  W Center Sect 15,13  W II II 56,411  W From N Side of 1313  W From Last N From Last N From Jast Stone Set N From Jast Stone Set			Bearings,	row Last Stone Bet North Ind 3	ine +	Thorn	8" /2"	9 89° 30'W 9 89° E	32,611	